

Over 90% of damage to facility doors occurs at the edges.

Only Acrovyn® Doors are available with replaceable stiles.

Ram Impact Tests\* prove the Acrovyn Door's superiority.




Acrovyn®

At a 8" drop a slight indentation in the Acrovyn occurred.



HPL

At a 4" drop the HPL laminate chipped, exposing sharp edges.



Wood

At a 3" drop the wood veneer chipped, exposing sharp edges.

\* Variations of ASTM F476-76 standard test methods for security of swinging door assemblies.



**Strength and Rigidity**

Crossbanding adds strength and rigidity to the door.

**Factory Sealed**

Top and bottom rails feature structural composite lumber and are factory sealed with an approved sealant.

**Removable Primary Stiles**

Beds, X-ray carts and people lifters can do more than just surface damage. That is why Acrovyn Doors feature replaceable stiles on doors up to 60 minute fire ratings. If ever damaged they can be replaced easily and onsite.

**Simply the Most Durable Door**

Wood veneer and high pressure laminate just can't handle the same abuse as durable Acrovyn. Acrovyn has withstood 45 years of abuse in tens of thousands of hospitals and schools worldwide.

**Field Replaceable Acrovyn Door Edges**

Field replaceable Acrovyn or stainless steel edges wrap around both the latch and hinge stiles for ultimate edge protection. Door edges are radiused for required impact protection.